Polishing Equipments



Order No.	Model No.	Type	Specification	Quantity	JPY	Ref.No
2-7694-01	Hairline Pad	Aluminum Oxide	# 60	1box(10sheets)	¥4,200	024435
2-7694-02	Highpad		#150	1box (5sheets)	¥4,700	024435
2-7694-03	7440		#180	1box	¥5,600	024435
2-7694-04	7446	Silicon Carbide	# 220	(10sheets)	¥4,200	024435
2-7694-05	7447	Aluminum Oxide	#320	1box (20sheets)	¥6,200	024435
2-7694-06	8447		# 280		¥ 6,200	024435
2-7694-07	8448	Silicon Carbide	#400		¥6,200	024435
2-7694-08	7448		#800		¥ 6,200	024435
2-7694-11	Pad	Holder #	961	1box(1piece)	¥1,300	024435

■ Specification

• Size : Pad Holder #961/82×118mm. Others/150×230mm

JP ■ Applications

Model No.	Applications			
Hair line pad	Descaling or Cleaning Steel, Cleaning Concrete.			
High pad	Descaling, Stripping Paint, Rough-polishing Stainless Steel or Aluminum Product.			
7440	Stripping Oxide Film or Paint, Hair-line Finishing Stainless Steel.			
7446	Removing Wood Coating Lints.			
7447	Descaling, Cleaning, Smoothing Scratches on Aluminum Product, Rough- polishing before Hair-line Finishing, Paint-coating, or Lamination.			
8447	Descaling, Cleaning, and Removing Stubborn Adherents from Cast and Wrought Products.			
8448	Finishing after Cleaning PCBs or Nonferrous Metals.			
7448	Finishing Name Plates, Finishing before Plating Electronic Components, Frosting Woodwork Paint Surface, Smoothing Scratches on Stainless Steel, Aluminum, or Copper.			

Laboratory Related

Safety Protection Supplies

В

Polishers and Cutters

F Pumps

Laboratory Equipment

Life Science and Analysis

Bottles and Containers

Tools and Fixtures

Cleaning and Sterilization

Clean

A Chambers and Baths

Heating and Cooling Equipment

C Mixers and Shakers

D Grinders

Uniwool

Order No.	Particle size	Color	Dimensions	Quantity	JPY	Ref.No
3-1864-02	# 800	Purple	450		¥ 2,500	024475
3-1864-03	#1500	Green	150× 230mm	1 box (10 sheets)	¥ 2,500	024475
3-1864-04	#3000	Grav	2301111	(TO SHEELS)	¥ 2.500	024475

- Feature The fine structure of a special fiber compound makes Uniwool perfect for scuffing before coating, or for polishing difficult uneven surfaces, such as the inner side of a door, roof gutters, or front grilles.
- Specification Material: Abrasive particles/CC, base material/unwoven fabric with a special fiber compound

- Specification Material: PA (nylon) (with grinding particles) Dimensions: 100×160mm

■ Applications • Oxidized coating and rust removal • Scuffing before coating Removing burnt deposit from welded parts Removing old coating



■ Feature ● Sand Magic is made of extra thick PA (nylon) unwoven fabric with abrasive particles for polishing, and is suitable for rust or paint that is hard to remove.

Very coarse

Grip Sander

Order No.	Model No.	Particle size	Quantity	JPY	Ref.No
3-1797-01	Very coarse	# 80	1 Box	¥7,800	024475
3-1797-02	Coarse	#120	(12 Pieces)	¥7.800	024475

■ Feature

- This tool is ideal for removing paint or rust.
- The grip makes it safe and easy to use.

Specification

- Material: abrasive/PA(nylon) unwoven fabric (with grinding particles), grip /PP (polypropylene)
- Dimensions:80×140×75mm

Applications

- To polishing woodworking materials, sealing and polishing coated surfaces
- To preliminary polishing prior to metalic coating
- To removing coating films
- To removing contamination from FRP and plastic
- To hairline finish and satin finish
- To decorative finish on metal

and resur						
SPONGE ABRASIVES						
Order No.	Model No.	Fitting No.	Dimensions	JPY	Ref.No	
2-7696-01	5081	# 120~# 180	114×140× 5tm	¥ 220	024475	
2-7696-02	5082	# 240~# 320		¥ 220	024475	
2-7696-03	5083	# 320~# 600		¥ 220	024475	
2-7696-04	5084	# 800~#1000		¥ 220	024475	

#1200~#1500

2-7696-05 5085 ※ The price is per sheet.

■ Feature

 Aluminum oxide abrasive grains are applied on special sponge to achieve abrading force and flexibility.

¥ 220

024475

• These products hardly clog, and are washable.