

APEM

Switches & Pilot Lights

Control Boxes

Emergency Stop Switches

Enabling Switches

Safety Products

Explosion Proof

Terminal Blocks

Relays & Sockets

Circuit Protectors

Power Supplies

LED Illumination

Controllers

Operator Interfaces

Sensors

AUTO-ID

Flush Silhouette

ø16

ø22

ø30

Miniature

Pilot Lights

HW

TW

YW

Maintenance Parts

All dimensions in mm.

When ordering, specify the Ordering No.

Shape		Material/Dimensions	Part No.	Ordering No.	Package Quantity	Remarks
Marking Plate	Round flush 	Acrylic ø21.5 Thickness = 1	HW9Z-P11	HW9Z-P11PN05	5	<ul style="list-style-type: none"> <li>• White</li> <li>• See B-225 for dimensions and engraving area.</li> </ul>
	Round extended 	Acrylic ø21.3 Thickness = 6.5	HW9Z-P12	HW9Z-P12PN05	5	
	Square flush 	Acrylic 22.7 Thickness = 1	HW9Z-P21	HW9Z-P21PN05	5	
	ø29/40 mm mushroom 	Acrylic ø15.7 H3.4	ALW3B	ALW3BPN05	5	
Operator Knob for Illuminated Selector Switch 	AS resin		HW9Z-FDY*-K	HW9Z-FDY*-K	1	<ul style="list-style-type: none"> <li>• Specify a color code in place of *.</li> <li>R (red), G (green), Y (yellow), A (amber), W (white), S (blue)</li> <li>• Use W (white) knob/lever for pure white illumination.</li> </ul>
Operator Lever for Illuminated Selector Switch 			HW9Z-FDL*-K	HW9Z-FDL*-K	1	
Spare Key (Disc Tumber Key) 	Metal (nickel-plated brass)		HW9Z-SK-231	HW9Z-SK-231PN02	2	
Spare Key (Pin Tumber Key) 	Metal (nickel-plated brass)		LW9Z-SK-500	LW9Z-SK-500PN02	2	• Standard key number
			LW9Z-SK-□	LW9Z-SK-□PN02		• Key number □ : 501 to 503
			LW9Z-SK-□	LW9Z-SK-□PN02		• Key number □ : 504 to 515
Lockig Ring 	Polyamide (black) ø28.4 H5 M22P1		HW9Z-LN	HW9Z-LNPN05	5	
Cap for Mono-lever Switch 	Standard	Nitril rubber ø10 L20	HW9Z-CPM	HW9Z-CPM	1	
Boot for Mono-lever Switch 	Standard	Nitril rubber ø29.2 L34.4	HW9Z-BLM	HW9Z-BLM	1	
Diffusing Lens 		Polycarbonate ø22.2 H21	HW9Z-PP5C	HW9Z-PP5C	1	• Used for LED type jumbo dome pilot lights only. Do not use for incandescent lamp illumination.
Safety Lever Lock 		Polyacetal (yellow)	HW9Z-LS	HW9Z-LSPN10	10	• A safety lever lock is supplied with a standard HW series switch/pilot light.
Gasket 		Nitril rubber (black)	HW9Z-WM	HW9Z-WMPN10	10	 <p>Thickness = 0.5</p> <p>ø21.6 ±0.15</p> <p>ø28.0 ±0.15</p>
Contact Block Plug 		Polyamide	HW9Z-CBPL	HW9Z-CBPLPN10	10	• Used to plug the hole in the center of contact block.

