

中荷重  
중하중  
MEDIUM LOAD



하중 荷重 ±10%  
직각도 直角度 2° 以下  
자유장 自由長 50m/m 以下 ±0.5m/m  
55m/m 以上 ± 1%

呼稱 호칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)	
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
CM 60×60	60	30	60	37.40	19.2	720	17.3	648	15.4	576
70			70	32.10	22.4		20.2		17.9	
80			80	28.12	25.6		23.0		20.5	
90			90	25.00	28.8		25.9		23.0	
100			100	22.50	32.0		28.8		25.6	
125			125	18.00	40.0		36.0		32.0	
150			150	15.00	48.0		43.2		38.4	
175			175	12.85	56.0		50.4		44.8	
200			200	11.25	64.0		57.6		51.2	
225			225	10.00	72.0		64.8		57.6	
250			250	9.00	80.0		72.0		64.0	
275			275	8.18	88.0		79.2		70.4	
300			300	7.50	96.0		86.4		76.8	
350			350	6.43	112.0		100.8		89.6	
CM 70×70			70	38.5	70		37.9		22.4	
80	80	33.2			25.6	23.0	20.5			
90	90	29.5			28.8	25.9	23.0			
100	100	26.6			32.0	28.8	25.6			
125	125	21.3			40.0	36.0	32.0			
150	150	17.7			48.0	43.2	38.4			
175	175	15.2			56.0	50.4	44.8			
200	200	13.3			64.0	57.6	51.2			
225	225	11.8			72.0	64.8	57.6			
250	250	10.6			80.0	72.0	64.0			
275	275	9.7			88.0	79.2	70.4			
300	300	8.9			96.0	86.4	76.8			
350	350	7.6			112.0	100.8	89.6			