

極重荷重
극중하중
EXTRA HEAVY LOAD

CB

하중 荷重 ±10%
직각도 直角度 2° 以下
자유장 自由長 50m/m 以下 ±0.5m/m
55m/m 以上 ± 1%

呼稱 호 칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)				
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load			
CB 6×15	6	3	15	6.00	18	3.0	2.7	16	2.4	14			
20			20	4.50							4.0	3.6	3.2
25			25	3.60							5.0	4.5	4.0
30			30	3.00							6.0	5.4	4.8
35			35	2.60							7.0	6.3	5.6
40			40	2.30							8.0	7.2	6.4
45			45	2.00							9.0	8.1	7.2
50			50	1.80							10.0	9.0	8.0
55			55	1.60							11.0	9.9	8.8
60			60	1.50							12.0	10.8	9.6
CB 8×10	8	4	10	16.94	33	2.0	1.8	30	1.6	26			
15			15	11.30							3.0	2.7	2.4
20			20	8.47							4.0	3.6	3.2
25			25	6.78							5.0	4.5	4.0
30			30	5.65							6.0	5.4	4.8
35			35	4.84							7.0	6.3	5.6
40			40	4.24							8.0	7.2	6.4
45			45	3.77							9.0	8.1	7.2
50			50	3.39							10.0	9.0	8.0
55			55	3.08							11.0	9.9	8.8
60			60	2.82							12.0	10.8	9.6
65			65	2.61							13.0	11.7	10.4
70			70	2.42							14.0	12.6	11.2
75			75	2.26							15.0	13.5	12.0
80			80	2.12							16.0	14.4	12.8
CB 10×10	10	5	10	22.78	45	2.0	1.8	41	1.6	36			
15			15	15.19							3.0	2.7	2.4
20			20	11.25							4.0	3.6	3.2
25			25	9.00							5.0	4.5	4.0
30			30	7.50							6.0	5.4	4.8
35			35	6.43							7.0	6.3	5.6
40			40	5.63							8.0	7.2	6.4
45			45	5.00							9.0	8.1	7.2
50			50	4.50							10.0	9.0	8.0
55			55	4.09							11.0	9.9	8.8
60			60	3.75							12.0	10.8	9.6
65			65	3.47							13.0	11.7	10.4
70			70	3.21							14.0	12.6	11.2
75			75	3.00							15.0	13.5	12.0
80			80	2.82							16.0	14.4	12.8
90	90	2.50	18.0	16.2	14.4								
100	100	2.25	20.0	18.0	16.0								
125	125	0.80	25.0	22.5	20.0								