

極重荷重
극중하중
EXTRA HEAVY LOAD

CB

하중 荷重 ±10%
직각도 直角度 2° 以下
자유장 自由長 50m/m 以下 ±0.5m/m
55m/m 以上 ± 1%

呼稱 호 칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)				
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load			
CB 35×35	35	17.5	35	69.94	490	7.0	490	441	392	392			
40			40	61.25							8.0	6.3	5.6
45			45	54.44							9.0	7.2	6.4
50			50	49.00							10.0	8.1	7.2
55			55	44.54							11.0	9.0	8.0
60			60	40.83							12.0	9.9	8.8
65			65	37.69							13.0	10.8	9.6
70			70	35.00							14.0	11.7	10.4
75			75	32.67							15.0	12.6	11.2
80			80	30.62							16.0	13.5	12.0
90			90	27.22							18.0	14.4	12.8
100			100	24.50							20.0	16.2	14.4
125			125	19.60							25.0	18.0	16.0
150			150	16.33							30.0	22.5	20.0
175			175	14.00							35.0	27.0	24.0
200			200	12.25							40.0	31.5	28.0
				36.0	32.0								
CB 40×40	40	20	40	80.00	640	8.0	640	576	512	512			
45			45	71.11							9.0	7.2	6.4
50			50	64.00							10.0	8.1	7.2
55			55	58.18							11.0	9.0	8.0
60			60	53.33							12.0	9.9	8.8
65			65	49.23							13.0	10.8	9.6
70			70	45.71							14.0	11.7	10.4
75			75	42.67							15.0	12.6	11.2
80			80	40.00							16.0	13.5	12.0
90			90	35.55							18.0	14.4	12.8
100			100	32.00							20.0	16.2	14.4
125			125	25.60							25.0	18.0	16.0
150			150	21.33							30.0	22.5	20.0
175			175	18.28							35.0	27.0	24.0
200			200	16.00							40.0	31.5	28.0
225			225	14.22							45.0	36.0	32.0
250	250	12.80	50.0	40.5	36.0								
275	275	11.64	55.0	45.0	40.0								
300	300	10.67	60.0	49.5	44.0								
				54.0	48.0								
CB 50×50	50	25	50	100.00	1000	10.0	1000	900	800	800			
55			55	90.91							11.0	9.0	8.0
60			60	83.33							12.0	9.9	8.8
65			65	76.92							13.0	10.8	9.6
70			70	71.42							14.0	11.7	10.4
75			75	66.67							15.0	12.6	11.2
80			80	62.50							16.0	13.5	12.0
90			90	55.55							18.0	14.4	12.8
100			100	50.00							20.0	16.2	14.4
125			125	40.00							25.0	18.0	16.0
150			150	33.33							30.0	22.5	20.0
175			175	28.57							35.0	27.0	24.0
200			200	25.00							40.0	31.5	28.0
225			225	22.22							45.0	36.0	32.0
250			250	20.00							50.0	40.5	36.0
275			275	18.18							55.0	45.0	40.0
300	300	16.66	60.0	49.5	44.0								
350	350	14.29	70.0	54.0	48.0								
				63.0	56.0								