


CoroMill® Century insert for milling

Advanced cutting materials

KRINS


90°

R/L590..H-P..-NL



90°

R/L590..H-P..-NW / R/L590..H-R..-NW




| | | | | | | | N Dimensions, mm, inch | | | | |
|-------|-----|-----|------|---------------------|---------------------|---------------------|------------------------|------|------|------|------|
| | | SSC | RE | KCH | CHW | BS | Ordering code | CD10 | W1 | LE | S |
| Light | | 11 | | 45° | 1.0 | 6.3 | L590-1105H-RC2-NW | ☆ | 11.5 | 3.0 | 5.00 |
| | | | | | .039 | .248 | | | .453 | .118 | .197 |
| | | | | 45° | 0.1 | 7.0 | L590-1105H-RS2-NW | ☆ | 11.5 | 3.0 | 5.00 |
| | | | | | .004 | .276 | | | .453 | .118 | .197 |
| | | | 0.4 | | | 6.8 | R/L590-1105H-RR2-NW | ☆ | 11.5 | 3.0 | 5.00 |
| | | | .016 | | | .268 | | | .453 | .118 | .197 |
| | | 11 | | 45° | 1.0 | 1.5 | R/L590-1105H-PC2-NL | ☆ | 11.5 | 3.0 | 5.00 |
| | | | | | .039 | .059 | | | .453 | .118 | .197 |
| | | | 45° | 1.0 | 1.5 | R/L590-1105H-PC5-NL | | ☆ | 11.5 | 6.0 | 5.00 |
| | | | | | | .039 | .059 | | | .453 | .236 |
| | | 0.4 | 0.0 | 2.2 | R/L590-1105H-PR2-NL | | ☆ | 11.5 | 3.0 | 5.00 | |
| | | | | | .016 | .000 | .087 | | .453 | .118 | .197 |
| 0.4 | | 0.0 | 2.2 | R/L590-1105H-PR5-NL | | ☆ | 11.5 | 6.0 | 5.00 | | |
| | | | | .016 | .000 | .087 | | .453 | .236 | .197 | |
| | | 45° | 0.1 | 2.2 | R/L590-1105H-PS2-NL | | ☆ | 11.5 | 3.0 | 5.00 | |
| | | | | | .004 | .087 | | | .453 | .118 | .197 |
| | 45° | 0.1 | 2.2 | R/L590-1105H-PS5-NL | | ☆ | 11.5 | 6.0 | 5.00 | | |
| | | | | .004 | .087 | | | .453 | .236 | .197 | |
| | 11 | | 45° | 1.2 | 6.0 | R590-1105H-RC2-NW | ☆ | 11.5 | 3.0 | 5.00 | |
| | | | | .047 | .236 | | | .453 | .118 | .197 | |
| | | | | 0.3 | 7.0 | R590-1105H-RS2-NW | ☆ | 11.5 | 3.0 | 5.00 | |
| | | | | .010 | .276 | | | .453 | .118 | .197 | |

Q5



J474



J508



Q1



Q17

