


SGコレット



下記の標準口径以外の特殊口径、及び寸法口径のコレットも製作致しますので、ご用命下さい。

単位:mm

型番	ツカミ能力 d	口径有効長さ ℓ	外径 D	長さ L	質量 (g)	型番	ツカミ能力 d	口径有効長さ ℓ	外径 D	長さ L	質量 (g)
SG6-	1.0	8.0	10.15	18.5	7	SG12-	5.0	19.4	17.9	32.5	33
	1.5	10.1			7		5.5	19.6			33
	2.0	11.3			7		6.0	21.7			33
	2.5	11.9			7		6.2	21.8			33
	3.0	12.1			6		7.0	22.0			32
	3.175	12.1			6		8.0	22.8			31
	4.0	13.4			5		8.5	22.9			30
	5.0	13.7			15		9.0	23.1			29
	5.5	13.8			5		10.0	24.9			27
	6.0	18.5			4		10.5	25.0			26
SG8-	1.0	7.9	12.8	23.5	13	SG16-	3.0	17.2	22.8	37.0	61
	1.5	10.6			13		12.0	32.5			22
	2.0	10.7			13		12.5	32.5			20
	2.5	11.9			13		4.0	20.0			63
	3.0	14.0			12		6.0	22.1			63
	3.175	14.0			12		8.0	24.1			62
	4.0	15.8			12		10.0	26.2			59
	5.0	16.1			11		12.0	27.8			55
	5.5	16.2			11		16.0	37.0			39
	6.0	17.9			11		SG20-	3.0			17.0
SG10-	2.0	11.1	15.3	28.0	10	4.0	20.3	27.6	41.0	99	
	2.5	11.8			9	6.0	22.8			100	
	3.0	13.9			20	8.0	26.0			102	
	3.175	13.9			20	10.0	27.1			98	
	4.0	16.7			20	12.0	30.1			98	
	5.0	17.0			20	16.0	32.3			82	
	5.5	17.1			20	20.0	41.0			57	
	6.0	19.3			20	SG25-	6.0			23.0	166
	6.2	19.3			20	8.0	26.0			170	
	7.0	19.6			19	10.0	27.1			170	
SG12-	3.0	16.8	17.9	32.5	19	12.0	32.0	41.5	58.5	176	
	3.175	16.8			19	16.0	37.8			166	
	4.0	19.1			18	20.0	42.0			142	
					17	25.0	50.0			93	
					16	SG32-	16.0			38.3	320
					14	20.0	42.0			300	
					33	25.0	47.9			262	
					33	32.0	58.5			158	
					33						

◆コレット呼び径に対して、-0.05mm以下では振れ精度の保障が出来なくなります。
◆コレット呼び径に対して、-0.1mmまではチャックできます。