

Shaft Supports T-Shaped Set Screw (Machined)

Standard / Wide

■ **Features:** Dowel Hole Type enables easy positioning in assembly.

■ **Standard**

🔗 Assembly Examples **REF P.232**

· W/o Dowel Hole

· With Dowel Hole

W/o Dowel Hole	With Dowel Hole	Material	Surface Treatment	Accessory
Height H Selectable	Height H Configurable	Height H Selectable		
SHTB	SHTBH / SHTBK	S45C Equivalent	Black Oxide	Hex Socket Set Screw 1 pc.
SHTM	SHTMH / SHTMK		Electroless Nickel Plating	
SHTS	SHTSH / SHTSK	SUS304	-	Hex Socket Set Screw 1 pc. (SUS)
SHTA	SHTAH	Aluminum Alloy	Clear Anodize	

Part Number	H		L	H ₁	T	S	W	Set Screw M	L ₁	d	Q	ℓ ₁	Unit Price											
	Type	D											W/o Dowel Hole		With Dowel Hole									
													Height H Selectable Type	Height H Configurable Type	Height H Selectable Type	Height H Configurable Type								
W/o Dowel Hole	3	10	15	20	26	8	4	10	M3	18	3.5	-	-	-	-	-	-	-	-	-				
		15	20	25										-	-	-	-	-	-	-				
		20	-	-										-	-	-	-	-	-	-				
	Height H Selectable	5	15	20	25	42	10	6	18	M4	30	4.5	4	5	-	-	-	-	-	-	-			
			20	25	30										40	-	-	-	-	-	-			
			25	30	40										50	-	-	-	-	-	-			
			30	40	50										60	-	-	-	-	-	-			
	Height H Configurable	8	10	15	20	54	16	8	35	M6	50	6.6	5	7	-	-	-	-	-	-	-			
			15	20	25										30	40	50	60	-	-	-	-	-	-
			20	25	30										40	50	60	-	-	-	-	-	-	
25			30	40	50										60	-	-	-	-	-	-	-		
With Dowel Hole	25	20	25	30	67	20	10	45	M6	65	9	5	7	-	-	-	-	-	-	-				
		30	40	50										60	-	-	-	-	-	-	-			
		40	50	60										80	-	-	-	-	-	-	-			
	SHTBK	35	25	30	40	85	15	75	100	M8	100	14	-	-	-	-	-	-	-	-	-			
			30	40	50										60	-	-	-	-	-	-	-		
			40	50	60										80	-	-	-	-	-	-	-		
			50	-	-										-	-	-	-	-	-	-	-		

🔗 H dimensions in () are applicable to w/o Dowel Hole Type only. 🔗 Dowel Hole Type is applicable to D dimensions 8 ~ 40 only.

■ **Features:** T dimension is thicker in comparison to Standard Type (I.D. D x1 ~ 1.5). Aluminum products are suitable for weight saving.

■ **Wide**

RoHS10

· D8~25

· D30~50

Type	Material	Surface Treatment	Accessory
SHTBN	S45C Equivalent	Black Oxide	Hex Socket Set Screw 1 pc.
SHTMN		Electroless Nickel Plating	
SHTSN	SUS304	-	Hex Socket Set Screw 1 pc. (SUS)

🔗 D dimensions 30 ~ 50 come with 2 screws.

Part Number	H		L	H ₁	T	S	W	Set Screw M	L ₁	d	Unit Price								
	Type	D									Selection	SHTBN	SHTMN	SHTSN					
SHTBN	8	10	15	20	42	15	6	18	M6	30	6.6	-	-	-					
		25	30	40								-	-	-					
		50	60	80								-	-	-					
		10	15	20								25	30	40	50	60	-	-	-
		12	15	20								25	30	40	50	60	-	-	-
		13	15	20								25	30	40	50	60	-	-	-
		15	15	20								25	30	40	50	60	-	-	-
		16	15	20								25	30	40	50	60	-	-	-
		20	20	25								30	40	50	60	80	-	-	-
		25	20	25								30	40	50	60	80	-	-	-
SHTMN	30	25	30	40	85	35	10	45	M8	65	6.6	-	-	-					
		40	50	60								80	-	-	-				
		50	60	80								-	-	-					
		35	25	30								40	50	60	80	-	-	-	
		40	30	40								50	60	80	-	-	-		
		50	40	50								60	80	-	-	-			
SHTSN	40	30	40	50	100	40	15	75	M8	80	9	-	-	-					
		50	40	50								60	80	-	-	-			

🔗 Ordering Example

Part Number	-	H
SHTB8	-	25
SHTMH15	-	25.6
SHTBN35	-	50