

Photo Sensor Cams

Plastic, Clamping, 180 deg., Angle Adjustable

Plastic

Type	M	Material	S	Surface Treatment	A	Accessory
HPJC		Polycetal (Black)	-	-	Set Screw	2 pcs.

RoHS10

Part Number		P Selection				M	A	B	C	S	t	Unit Price	Volume Discount Rate
Type	D											1 ~ 9 pc(s).	10~50
HPJC	32	5	6	8	M3	5.5	14	8.5	1.5	1.5			
	40	5	6	8									
	40	10	12	M4	20	2							
		50	6				8	M3	7.5		25	2.5	
50	10	12	15	M4									

Ordering Example: Part Number - P
HPJC40 - 6

Clamping

Type	M	Material	S	Surface Treatment	A	Accessory
HPSCC		A6063	-	Black Anodize	Hex Socket Head Cap Screw	

RoHS10

Part Number		P Selection				A	m	B	C	S	X	Y	t	Unit Price	Volume Discount Rate
Type	D													1 ~ 9 pc(s).	10~50
HPSCC	50	8	10	12	15	11	4.75	31	6.5	2.5	11.5	4.8	1.5		

Ordering Example: Part Number - P
HPSCC50 - 15

180 deg.

Type	M	Material	S	Surface Treatment	A	Accessory
PSC		Nylon 6 (Glass Fiber 30%)	-	-	Set Screw	
PSCH		A6063	-	Black Anodize	Set Screw	3 pcs.

RoHS10

Part Number		B	D	PSC		PSCH	
Type	P			Unit Price	Volume Discount Rate	Unit Price	Volume Discount Rate
				1 ~ 9 pc(s).	10~50	1 ~ 9 pc(s).	10~50
PSC PSCH	6	13	28				
	8	15	30				
	10	17	32				
	12	19	34				

Ordering Example: Part Number
PSC10

Features: Slit angle can be adjusted after installation.

Angle Adjustable

Type	Part	M	Material	S	Surface Treatment	A	Accessory
HPSCA	Main Body		A6063	-	Black Anodize	Set Screw	2 pcs.
	Angle Adjustable Plates		A5052	-	-		

RoHS10

Part Number		P Selection				Z Adjustment Range	M	A	B	C	Effective Slit Depth*	Unit Price	Volume Discount Rate
Type	D											1 ~ 9 pc(s).	10~50
HPSCA	40	5	6	8	10~120	M3	5.5	20	6	5.5mm			
		10	12	M4									
	50	6	8		M3	7.5	25	8.5	6.8mm				
		10	12	15						M4			

* Effective slit depth is shallower than C because of the adjustment screw (and slot).

Ordering Example: Part Number - P
HPSCA40 - 12